

C-17 Cast Iron Vertical Inverted Bucket Type Steam Trap

Description

- NETA Cast Iron Vertical Inverted Bucket Type Steam Trap
- With 18/8% Cr/Ni (AISI-304) Bucket
- Screwed Female Ends
- BSP Parallel Threads

Test Pressure

Max. Working Pressure : 150 PSIG
 Max. Working Temperature : 220°C
 Test Pressure : 300 PSIG Hyd.

Certification

IBR Test Certificate in FORM III-C duly signed by the Director of Boilers, Punjab is provided.

Application : Steam

HSN : 84818010



Materials

PNo.	Part	Nos.	Material	Standard
1	Plug	1	Bronze	IBR 282[a][iv] Gr.B
2	Cover	1	C.I.	IBR 86 to 93 Gr.A
3	Body Cover Nuts and Bolts	To Suit	M.S.	IS:1367
4	Valve Seat	1	S.S. 13% Cr.	ASTM A182 Gr.F6a / AISI - 410
5	Valve	1	S.S. 18/8% Cr./Ni	AISI - 304
6	Valve Locking Washer	1	S.S. 18/8% Cr./Ni	AISI - 304
7	Bucket	1	S.S. 18/8% Cr./Ni	AISI - 304
8	Body	1	C.I.	IBR 86 to 93 Gr.A
9	Bucket Ring	1	C.I.	IBR 86 to 93 Gr.A
10	Lever Holder	1	S.S. 18/8% Cr./Ni	AISI - 304
11	Valve Lever	1	S.S. 18/8% Cr./Ni	AISI - 304
12	Gasket	1	C.A.F.	IS:2712
13	Bucket Hook	1	S.S. 18/8% Cr./Ni	AISI - 304

Dimensions

Nominal Size (Inches)	Nominal Size (mm)	H Max.	T
1/2	15	184	1/2
3/4	20	213	3/4
1	25	286	1
1.1/4	32	335	1.1/4
1.1/2	40	391	1.1/2
2	50	451	2

SINCE 1955



ISO 9001:2015 & ISO 14001:2015 CERTIFIED

