

572/5 Gun Metal Wheel Valve No.5 Screwed Ends

Description

- NETA Gun Metal Wheel Valve No.5
- Heavy Pattern
- Screwed in Bonnet
- Inside Screw
- Rising Stem
- Screwed Female BSP Parallel Ends
- Handwheel Operated

Test Pressure

Hyd. Test Pressure : 35 Kg/cm²

Certification

Our Works Test Certificate

Application : Water

HSN : 84818020



Materials

PNo.	Part	Nos.	Material	Standard
1	Handwheel Nut / Set Screw	1	M.S.	IS:1367
2	Washer	1	M.S.	IS:226
3	Handwheel	1	C.I. / M.S.	IS:210 Gr.FG200 / IS:226
4	Stem	1	Brass	IS:6912 Gr.FLB
5	Gland Nut	1	G.M.	IS:318 Gr.LTB2
6	Gland Packing	-	Asbestos	IS:4687
7	Disc	1	G.M.	IS:318 Gr.LTB2
8	Body	1	G.M.	IS:318 Gr.LTB2
9	Gland	1	G.M.	IS:318 Gr.LTB2
10	Bonnet	1	G.M.	IS:318 Gr.LTB2
11	Disc Nut	1	G.M.	IS:318 Gr.LTB2

Dimensions

Nominal Size (Inches)	Nominal Size (mm)	L ±1.5	H App.	W App.	T - BSP Parallel Threads
1/2	15	55	78	54	1/2
3/4	20	66	96	60	3/4
1	25	78	115	76	1
1.1/4	32	85	125	76	1.1/4
1.1/2	40	100	130	90	1.1/2
2	50	123	158	108	2
2.1/2	65	140	185	118	2.1/2
3	80	162	204	130	3
4	100	180	250	163	4

