

## NMW-14 Bronze Spring Relief Valve Straight Type

### Description

- Neta Bronze Spring Relief Valve, Straight Type
- Open Discharge
- Screwed Male Inlet
- BSP Parallel Threads.

### Test Pressure

Max. Set Pressure - 150 PSIG (Hyd.)

Test Pressure - 300 PSIG (Hyd.)

### Certification

If required Works Test Certificate shall be provided.

**Application : Steam, Air**

**HSN : 84818020**



### Materials

PNo.	Part	Nos.	Material	Standard
1	Adjusting Screw	1	G.M.	IS:318 Gr. LTB2
2	Check Nut	1	G.M.	IS:318 Gr. LTB2
3	Spindle	1	Brass	IS:6912 Gr. FLB
4	Upper Spring Disc	1	G.M.	IS:318 Gr. LTB2
5	Spring	1	S.S. (AISI - 304)	IBR 307
6	Lower Spring Disc	1	G.M.	IS:318 Gr. LTB2
7	Spring Chamber	1	G.M.	IS:318 Gr. LTB2
8	Disc	1	G.M.	IS:318 Gr. LTB2
9	Body	1	G.M.	IS:318 Gr. LTB2

### Dimensions

Nominal Size (Inches)	Nominal Size (mm)	A	B	H
1/2	15	11	1/2"	138
3/4	20	15	3/4"	153
1	25	21	1"	160
1.1/2	40	33	1.1/2"	180
2	50	46	2"	223

