

NMW-23 Forged Brass Ball Valve, PN-25 Screwed Ends

Description

- Full Bore, Two Piece Design
- Hard Chrome Plated, Self Cleaning Brass Ball
- Premium Quality PTFE Body Seat Rings & Gland packing Rings
- Quarter Turn, Lever Operated
- Chrome Finish Body
- Blow-out Proof Stem
- Screwed Female Ends BSP (IS:554) Parallel Threads

Test Pressure

Hydraulic Test Pressure:

Body : 550 Psig

Seat : 350 Psig



Certification

Work Test Certificate can be issued, if required.

Application : Water, Oil, Air

HSN : 84818020

Materials

PNo.	Part	Nos.	Material	Standard
1	Lever Nut	1	Brass Chrome Plated	-
2	Lever	1	M.S.	IS:226
3	Stem	1	Forged Brass	IS:6912 Gr. FLB
4	Body Seat Ring	2	Teflon	PTFE / BS EN 12086-1
5	Ball	1	Forged Brass H Cr. Plated	IS:6912 Gr. FLB
6	Body	1	Forged Brass	IS:6912 Gr. FLB
7	Gland	1	Forged Brass	IS:6912 Gr. FLB
8	Lever Sleeve	1	PVC	-
9	Body Connector	1	Forged Brass	IS:6912 Gr. FLB
10	Gland Packing	-	Teflon	PTFE / BS EN 12086-1

Dimensions

Nominal Size (Inches)	Nominal Size (mm)	A±1.5	B BSP	E	H
1/2	15	52	1/2"	56	100
3/4	20	58	3/4"	63	100
1	25	66	1"	66	118
1.1/4	32	78.5	1.1/4"	77	137
1.1/2	40	87.5	1.1/2"	83	146
2	50	99	2"	94	146

