

NMW-15 Gun Metal Swing Check Valve Screwed Ends

Description

- Heavy Pattern
- Screwed in Cover
- Screwed Female BSP Parallel Thread Ends.
- The disc swings off the seat to allow forward flow and when the flow is stopped, the disc swings back onto the seat to block the reverse flow.

Test Pressure

Test Pressure : 300 PSIG Hyd.

Certification

If required Works Test Certificate shall be provided.

Application : Water



Materials

PNo.	Part	Nos.	Material	Standard
1	Cover	1	G.M.	IS:318 Gr. LTB2
2	Hinge Pin	1	Brass	IS:6912 Gr. FLB
3	Lever	1	G.M.	IS:318 Gr. LTB2
4	Soft Seat	1	Synthetic Rubber / Teflon	BS EN 12086-1
5	Disc	1	G.M.	IS:318 Gr. LTB2
6	Body	1	G.M.	IS:318 Gr. LTB2
7	Washer	1	Brass / M.S.	IS:6912 Gr. FLB / IS:1367
8	Bolt	2	Brass / M.S.	IS:6912 Gr. FLB / IS:1367

Dimensions

Nominal Size (Inches)	Nominal Size (mm)	L	T	H
1/2	15	50	1/2	36
3/4	20	60	3/4	42
1	25	74	1	48
1.1/4	32	88	1.1/4	48
1.1/2	40	98	1.1/2	60
2	50	105	2	73

