

IC-2 S.S Investment Casting (ASTM A351) Gr. CF-8 Disc Check Valve

Description

- S.S Investment Casting (ASTM A351) Gr. CF-8 Disc Check Valve (Non Slam Check Valve) Wafer Type PN-40
- Design standard DIN EN-558-2.
- Investment casting BODY, STAR, DISC.
- Metal to Metal Zero Leak Proof.
- Suitable for clamping between flanges as per ASME B16.5 Class-150, Class-300, PN-40.
- Size Range : 15mm – 50mm

Test Pressure

Body : 60 Bar (Hyd.)

Seat : 40 Bar(Hyd.)

Certification

IBR Test Certificate in Form III-C duly signed by the Director of Boilers, Punjab is provided.

Application : Steam, Water, Oil

HSN : 84818010

Materials

PNo.	Part	Nos.	Material	Standard
1	Body	1	S.S. 18/8% Cr./Ni.	ASTM A351 Gr. CF8
2	Disc	1	S.S. 18/8% Cr./Ni.	ASTM A351 Gr. CF8
3	Star (Yoke)	1	S.S. 18/8% Cr./Ni.	ASTM A351 Gr. CF8
4	Spring	1	S.S. 18/8% Cr./Ni.	S.S. (AISI-304)

Dimensions

Nominal Size (Inches)	Nominal Size (mm)	A	B	C	H
1/2	15	56	42	15	17
3/4	20	67	52	19	20
1	25	80	63	25	23
1.1/4	32	90	70	32	30
1.1/2	40	101	85	40	32
2	50	104	95	50	40

