

5(c) Bronze Globe Steam Stop Valve Straight or Right Angle Type, Flanged Table 'F' Ends

Description

- NETA Bronze Globe Steam Stop Valve Straight or Right Angle Type
- Outside Screw and Yoke Type
- Rising Stem with Back Seat
- Renewable 13% Cr. Stainless Steel (ASTM A182 Gr.F6a / AISI - 410) Trim
- Flanged BS-10 Table 'F' Ends
- Handwheel Operated

Test Pressure

Max. Working Pressure : 150 PSIG
 Max. Working Temperature : 220°C
 Test Pressure : 300 PSIG Hyd.

Design Features

- Valve Disc and Check Nut are locked in position by using S.S. (AISI-304) Locking Washer.
- Back seating arrangement permits the replacement of the gland packing in fully open position while the Valve is under in line pressure.
- Body design is rigid and extra sturdy and have smooth full flow area throughout the Valve Body.
- For longer life of Valve Seating Body Seat Ring and Disc are properly heat treated.



Certification

IBR Test Certificate in FORM III-C duly signed by the Director of Boilers, Punjab is provided for Valves to be used on steam service.
 For liquid service our own Works Test Certificate shall be issued.

Application : Steam, Water, Oil

HSN : 84818020

Materials

PNo.	Part	Nos.	Material	Standard
1	Handwheel Nut	1	M.S.	IS:1367
2	Washer	1	M.S.	IS:226
3	Handwheel	1	C.I./Al	IS:210 Gr.FG200 / BS:1490 Gr.LM-6
4	Bonnet	1	Bronze	IBR 282[a][iv] Gr.B
5	Stem	1	S.S. 13% Cr.	ASTM A182 Gr.F6a / AISI - 410
6	Gland	1	Bronze	IBR 282[a][iv] Gr.B
7	Packing	-	Graphited Asbestos	-
8	Gasket	1	C.A.F.	IS:2712
9	Disc	1	S.S. 13% Cr.	ASTM A182 Gr.F6a / AISI - 410
10	Body Seat Ring	1	S.S. 13% Cr.	ASTM A182 Gr.F6a / AISI - 410
11	Body	1	Bronze	IBR 282[a][iv] Gr.B
12	Studs for Gland	2	M.S.	IS:1367
13	Nuts for Gland	2	M.S.	IS:1367
14	Studs and Nuts for Body and Bonnet	4 Each	M.S.	IS:1367
15	Locking Washer	1	S.S. 18/8% Cr./Ni	AISI - 304
16	Check Nut	1	Bronze	IBR 282[a][iv] Gr.B

Dimensions

Nominal Size (Inches)	Nominal Size (mm)	L ±1.5	L1 ±1.5	H App.	H1 App.	W App.
1/2	15	71.5	103	108	120	90



Nominal Size (Inches)	Nominal Size (mm)	L ±1.5	L1 ±1.5	H App.	H1 App.	W App.
3/4	20	74.5	109	135	150	100
1	25	81.5	121	160	180	100
1.1/4	32	87.5	135	180	210	125
1.1/2	40	100.5	147	215	235	150
2	50	106.5	194	255	260	150
2.1/2	65	118.5	224	260	267	160
3	80	133.5	260	285	323	175

